**KYOWA** 

Manufacturer of Test Pumps & High-Pressure
Washing Machines — Offers

## TESTPUMP

## **HYDRAULIC PRESSURE TEST PUMP**





[HAND OPERATED] Model T-50K-P/T-100K

## SPECIFICATIONS (50kg/cm² pressure gauge is available if desired.)

Item Model	Maximum Pressure	Plunger Diameter	Stroke	Rate of Water Suction Per Stroke	Capacity of Water Tank	Size of Discharge Port	Weight	Dimensions L×H×W	Accessories
T-50K-P	5Mpa (50kg/cnl)	2211/16	35%	13cc	4.5£ Plastic tank	34	3.3kg	320×300 ×200‰	Pressure gauge 1,PT 1 Pressure hose 1 Union joint 1, 1 Bushing 1,×1, 1
T-100K	10Mpa (100kg/cml)	22%	35%	13cc	5.2£ Steel tank	1/4	7.0kg	370×300 ×210%	Pressure gauge SIPT 1 Ultire high pressure hose SIPF X Im 1 Is repple

\*SPecifications may be subject to change without notice. \*KYOWA's products are patented. Give careful attention to imitations

## FEATURES OF KYOWA TESTER

- 1. High-precision stainless steel (SUS 304) ball value is applied as the valve.
- 2. Valve seat is replaceable with ease.
- Water tank of rust-free plastic (P.P.) construction assures unchanging cleanliness. (Models T-50K and T-100K are of vinyl-coated steel sheet construction.)
- 4. The plunger packing used is standard product, O-ring No. P-22 which is available in local hardware dealers.
- 5. All fulcrum pins applied are made of stainless steel.
- 6. A full range of accessories are provided to permit on-the-spot job
- 7. Matchless compact and light-weight design in the world.